

Model G0077250 (50ST/Canada)
UPC: 696471079692

1 of 2



FEATURES

- **X-Frame - Fully Wrapped, Heavy Duty 11 Gauge Steel Frame** provides rugged durability and protects the hose connections from damage
- **Generac G-Force 265cc OHC engine** with low-oil shutdown
- **Large 2.9 gallon steel tank fuel tank** with incorporated fuel gauge provides up to 4.3 hours of run time
- **Steel Lifting Pocket** designed for easier lifting and transportation on jobsites by crane or forklift
- **Engraving Plate** allows unit to be tagged / cataloged for use in contractor and rental fleets
- **Color-coded suction and discharge ports** to ensure the correct hose connections. (Blue = Discharge; Green= Suction)
- **Easy Prime** custom funnel design for quick and easy priming
- **Durable silicon carbide mechanical seal** for long life
- **Onboard instructions** with icons of key touch points make this pump easy to use

Specifications

Engine Type	4 cycle/OHC
Engine Displacement (cc)	265
Start Type	Recoil Pull Start
Low Oil Shutdown Method	Low Level
Recommended Oil	10W-30 / SAE30
Fuel Capacity (gal/L)	2.9/10.9
Max Run Time	4.3 hrs
Max Flow gpm/lpm	350/1352
Max Total Head (ft/m)	90/27
Max Suction Lift (ft/m)	26/7.9
Mechanical Seal Type	Silicon Carbide
Solid Handling (in/mm)	1.2/30.48
Suction Port (in/mm) (NPT)	3/76.2
Discharge Port (in/mm) (NPT)	3/76.2
Pump Housing	Aluminum
Impeller	Ductile Cast Iron
Volute	Ductile Cast Iron

Strainer	Yes
Country of Origin	China
Warranty	3 Year
Assembled Length (L) (in/mm)	31.5/800
Assembled Width (W) (in/mm)	23.5/597
Assembled Height (H) (in/mm)	29.25/743
Unit Weight (lb/kg)	163/74
Carton Length (in/mm)	32.2/817
Carton Width (in/mm)	24.1/612
Carton Height (in/mm)	25.3/642
Shipping Weight (lb/kg)	173/78.5

